

IS-2C精密电子天平

precision balance

ISmart 艾斯玛特



- ★ LCD液晶显示/交直流两用
- ★ 全量程去皮/计数/单位转换(g/ct/oz)...
- ★ 最小起称量可调
- ★ 过载报警/水平指示器
- ★ 选购：双显/通讯串口/打印机/防风罩/防尘罩
- ★ 标配校准砝码
- ☆ LCD/AC and DC power supply
- ☆ Tare function/Counting/Unit conversion(g/ct/oz)...
- ☆ Min weighing set
- ☆ Overload alarm/Level indicator
- ☆ Option: Dual display/Interface/Printer/Windproof /Dust cover
- ☆ Standard calibration weights

产品参数 Product specifications

型号 Model	量程 Capacity	可读性 Readability	重复性 Repeatability	线性 Linearity	秤盘尺寸 Pan Size	稳定时间 Stable Time
IS100-2C	110g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS200-2C	210g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS300-2C	310g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS500-2C	510g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS600-2C	610g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS1000-2C	1100g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS2000-2C	2100g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S
IS3000-2C	3100g	0.01g	± 0.02g	± 0.03g	Φ 130mm	≤ 2S