

- ★全自动内部校准
- ★LCD液晶显示
- ★一键触发内校/全自动时间触发内校
- ★高科技材质键盘保护/压铸铝合金外壳/四面防静电涂层玻璃防风罩
- ★全量程去皮/计数/百分比称重等13种应用程序
- ★g/mg/ct/oz等13种计量单位转换
- ★灵敏度/速度可调/环境过滤器
- ★过载报警/故障报警/水平指示器
- ★全新一代高精度传感器
- ★动态温度补偿

- ☆ Internal auto calibration
- ☆ LCD (White back light with black font)
- ☆ One key/Time trigger internal calibration
- ☆ High-tech keyboard protection/die-cast aluminum housing/four-sided anti-static coated glass windproof hood
- ☆ Full scale peeling/counting/percentage weighing etc. 13 applications
- ☆ g/mg/ct/oz and other 13 units of measurement conversion
- ☆ Sensitivity/speed adjustable/environmental filter
- ☆ Overload alarm/fault alarm/level indicator
- ☆ A new generation of high-precision sensors
- ☆ Dynamic temperature compensation



## 产品参数 Product specifications

产品型号	Model	IS214AI	IS314AI	IS414AI	IS514AI	IS614AI	IS1104AI
最大称量	Capacity(g)	220g	310g	410g	510g	610g	1100g
精度	Resolution(g)	0.1mg					
稳定时间	Stable Time	≤2s					
显示方式	Display	LCD ( white back light with black font ) 白色背光黑色字体					
秤盘尺寸	Pan size	Φ80mm					
使用温度	Operation temp	5-35℃					
重复性	Repeat ability	0.1mg如果重量≤220g 0.3mg从220g到310g 0.35mg从310g-610g					
线性	Liner	±0.5mg					
防风罩尺寸	Draft shield Size	162mmx171mmx225mm					
校准砝码	Cal.weight	External ( Internal ) Calibration					
输出端口	Interface	RS232 ( 标配 ) RS485/打印机 ( 选配 )					
外形尺寸	Dimension	345mmx215mmx345mm					
毛净重	G.N.weight	7Kg					